

PREMIUM FEATURES

HIGH TEMPERATURES	Service rating over wide temperature range of -20 to +250°C
CHEMICALLY INERT	Non flammable, solvent & chemically resistant, oxygen compatible grease
REDUCES CONSUMPTION	Excellent resistance to thermal degradation, low evaporation & lasts longer
CORROSION PROTECTION	Offers extended protection from rusting & corrosion

MOLYSULF: INDUSTRIAL APPLICATIONS								
ASV PRODUCT	THICKENER / BASE OIL	BASE OIL VISCOSITY 40°C cSt	NLGI GRADE	DROP POINT °C	SERVICE RATING °C	COLOR	Lubrication of preheater, single facer, pressure & corrugator roll bearings exposed to high	
GREASE							temperatures & aggressive chemical	
FLUONOX COR 200	PTFE / PFPE	510	2	None	-20 to +250	Milky White	environments	

MOLYSULF

Manufactured by **ASV Multichemie Private Limited** W 46,TTC Industrial Area, MIDC Rabale Navi Mumbai 400 701 INDIA Contact +91 22 27642514 Marketing +91 22 27642515 Technical Assistance info@asymultichemie.com

www.asvmultichemie.com

ASV® MOLYSULF® BRIGHT ZINK® SHINY GALVA® PENETROIL® SPEZET® MOLY CHEM® TRIBOSULF® VALV-KOTE®