

ASV[®]



VALV KOTE[®] 60

SYNTHETIC LUBRICANT FOR PLUG & GATE VALVES

VALV KOTE[®] 60 valve lubricating sealant is a fully synthetic oil based inorganically thickened grease exhibiting exceptional resistance to sweet and sour (H₂S & CO₂) aliphatic hydrocarbons (liquids and gas), crude oil, condensates and natural gas.

VALV KOTE[®] 60 is inhibited against degradation by hydrogen sulphide (H₂S), oxidation, rust and corrosion. Service rating is between -40°C to +260°C.



PREMIUM FEATURES

- Fully Synthetic Infusible Grease
- Sweet & Sour Inhibited
- Contains Premium EP Additives & MoS₂
- High Load Carrying Capacity
- Protects Internal Surfaces From Wear
- Non Hardening Adhesive Film Stays Longer
- Seals Effectively Against High Pressures

MOLYSULF®							SUITABLE FOR
ASV PRODUCT	THICKENER	BASE OIL	COLOR	NLGI GRADE	DROP POINT °C	SERVICE RATING °C	Water, Gasoline, Fuel Oil, Crude Oil & Distillates, Natural Gas, Kerosene, Jet Fuel, Aqueous Solutions, Aliphatic Hydrocarbons (Liquid & Gas)
SYNTHETIC LUBRICANT FOR GATE & PLUG VALVES							
VALV KOTE 60	Inorganic	Synthetic	Dark Gray	2	None	-40 to +260	

MOLYSULF[®]

Manufactured by
ASV Multichemie Private Limited
W 46, TTC Industrial Area, MIDC Rabale
Navi Mumbai 400 701 INDIA

Contact
+91 22 27642514 Marketing
+91 22 27642515 Technical Assistance
info@asvmultichemie.com

www.asvmultichemie.com

ASV[®] MOLYSULF[®] BRIGHT ZINK[®] SHINY GALVA[®]
PENETROIL[®] SPEZET[®] MOLY CHEM[®] TRIBOSULF[®]
VALV-KOTE[®]
Registered Trademark of ASV MULTICHEMIE PRIVATE LIMITED, INDIA