



1. General description

Brake parts cleaner with five active components. Removes oil, grease, traffic dirt and brake fluid. Highly effective. Pleasant smell and handy 360° spray system. Fast drying, leaves no residue.



2. Features

- Effectively removes brake fluid, grease, oil and hardened deposits.
- Reduces disc-brake squeal and clutch chatter.
- Fast evaporation to minimize downtime.
- Does not leave a residue.
- Safe on all metal surfaces, does not stain.
- Safe on most rubbers, plastics and coatings. Test on sensitive or stressed materials before use.
- Convenient 360° (including inverted position) spray valve for aerosols.
- High purity CO2 propellant, giving an active product content of 95%.

3. Applications

- Perfect for cleaning and degreasing of all brake and clutch parts.
- Cleaning mechanical parts.

4. Directions



- Spray liberally and allow to run off.
 - Allow to dry at room temperature.
 - Repeat if necessary.
 - Use extension tube for more precise application.
 - Test before use on sensitive materials.
 - Do not use on energized equipment.
 - Do not use on sensitive electronic equipment.
 - Allow to dry completely before reactivation.
 - Use only with adequate ventilation.
 - Protect and re-lubricate if necessary.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

5. Typical product data (without propellant)

	Aerosol	Bulk
Appearance	Liquid.	Not available.
Color	Colorless.	Colorless.
Odor	Citrus.	Characteristic odor.
Density	0.712 g/cm ³ (@ 20°C).	0.712 g/cm ³ (@ 20°C).
Flash Point	< 0 °C	- 19 °C
Auto Ignition temperature	> 200 °C	> 200 °C
Evaporation rate	2.8 (Ether=1)	2.8 (Ether=1)
Vapor density	3 (@ 20°C).	3 (@ 20°C).
Surface tension active product	21 mN/m	Not available.

6. Packaging

Aerosol	12x500 ML	Ref. : 10347
	12x750 ML	Ref. : 32242
	24x500 ML	Ref. : 10347
	24x600 ML	Ref. : 30456
Bulk	2 L	Ref. : 32355
	20 L	Ref. : 10358
	200 L	Ref. : 30457
	60 L	Ref. : 30462





2x5 L

Ref. : 10355

7. Remarks

Sensitive plastics (e.g. polystyrenes and polycarbonates,) need to be checked, particularly when thermal or mechanical stress is involved.

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version CRC_RED-BRAKLEEN-20150424

Date



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com

