

SKL-SP2

Solvent Removable Visible Dye Penetrant

SKL-SP2 is a solvent removable visible red dye penetrant. SKL-SP2 locates surface-breaking discontinuities with a simple three-step process that is ideal for basic industrial nondestructive testing. SKL-SP2 features high-performance penetrating characteristics and produces clear vivid red indications.

SKL-SP2 is a reliable penetrant testing method for preventative maintenance and quality checks. SKL-SP2 is used to inspect welds, forgings, pressure vessels, castings, general metalwork and can be used in leak testing applications.

SKL-SP2 is listed on QPL-AMS-2644 as Type 2, Methods B, C, and D.



BENEFITS

Fastest inspection processing

- Reliable, simple 3-step process is a convenient and easy-to-use solution for preventative maintenance and control checks
- Quickly and completely covers the entire test surface due to high surface wetting
- Remove excess penetrant without water to eliminate the need to dry parts before applying developer

Dependable and convenient to use

- Easy to carry and use in the field with the convenient aerosol cans which are carefully designed for consistent, even coverage and maximum test area coverage
- Use in all conditions without the need for darkness or UV lights

Wide application versatility

- Inspect a wide range of components without fear of corrosion or specification non-conformance
- Meets AMS 2644 and is NDT-approved for professional industrial applications

Maximum indication detection

- Produces strong, vibrant indications thanks to the bright, vibrant red color, especially when used with SKD-S2 solvent-based developer

Maximize operator comfort and safety

- Promotes better inspection quality by providing the operator with a more comfortable work environment
- Reduces discomfort from strong odors
- Exceeds all EHS requirements, does not contain NPEs or phthalates

SPECIFICATION COMPLIANCE

- AECL
- AMS 2644
- ASME
- ASTM E1417
- ASTM E165
- ISO 3452
- MIL-STD-2132
- MIL-STD-271
- NAVSEA T9074-AS-GIB-010/271
- NAVSEA 250-1500-1
- QPL SAE AMS 2644

FEATURES

- Solvent removeable
- ISO 3452 sensitivity level #2
- Can be used for Method B, Method C and Method D
- Simple, easy-to-use process
- Vivid, high-contrast red color
- Superior flaw resolution
- Good surface wetting
- Optimized capillary action
- Works in visible light
- Very low toxicity
- Low odor
- NDT-spec compliant

PROPERTIES

Flash Point	> 200°F / 93°C
Density	0.85 g/cc / 7.04 lb/gal
Viscosity (at 100°F/38°C)	3.80 cs
NPE-Free	Yes

USE RECOMMENDATIONS

NDT Method	Penetrant Testing, Visible Dye
Type	Type 2
Method(s)	B / C / D
Sensitivity Level	ISO 3452 sensitivity level #2
Required Equipment	No special equipment needed
Usage Temperature	40 to 125°F / 5 to 52°C
Storage Temperature	50 to 86°F / 10 to 30°C
Coverage	1 gal will cover approximately 1,200 ft ² / 111 m ²

APPLICATIONS

Defect location: open to surface

Ideal for:

- Wide range of applications
- Castings
- Forgings
- Welds
- Pressure vessels
- Metalworking
- Automotive maintenance
- Tubular goods
- Leak testing
- Ferrous and non-ferrous metals
- Non-porous ceramics

Defect examples:

- Cracks
- Leaks
- Incomplete weld penetration
- Incomplete weld fusion
- Undercutting
- Slag inclusions
- Flux inclusions
- Weld porosity

PACKAGING

Aerosol can, case of 12	01-5155-78
1 gal / 3.78 L jug, case of 4	01-5155-35
5 gal / 18.9 L pail	01-5155-40
55 gal / 208 L drum	01-5155-45

HEALTH AND SAFETY

Review all relevant health and safety information before using this product. For complete health and safety information, refer to the product Safety Data Sheet, which is available at www.magnaflux.com.