

ML 2 EP GREASE

Lithium Soap Based Multipurpose Grease

Applications

- Use successfully for roller bearing, plain bearings, roller guides, threaded spindles, splined shafts, taper bearings, needle roller bearings, ball and socket joints, sliding and mating surfaces, journal bearings, couplings.
- For long lasting lubrication of cams, shafts, spring, joints, steel cables and similar equipment operating under light to medium loads and low to high speeds.

Benefits

- Extremely wide service temperature range of -25°C to +120°C
- Reduces friction and wear
- Low evaporation rate increases relubrication intervals
- High load carrying capacity
- Highly resistant to hot or cold water and water washout
- Offers good surface protection and corrosion inhibiting properties
- Good resistance to oxidation
- Can be dispensed via centralized lubrication systems

Directions for Use

Apply on all clean sliding surfaces by normal greasing methods i.e. by brush, grease gun or dispense via centralized lubrication systems. Do not mix with other oils or grease.

ML 2 EP GREASE

| TECHNICAL PROPERTY | | | |
|--------------------|-----------------------------|--------------------|---|
| Standard | Property | UNIT | VALUE |
| | Type | | Mineral oil, lithium soap and additives |
| | Appearance | | Smooth grease |
| | Color | | Yellowish |
| | Base Oil | | Mineral oil |
| ASTM D 445 | Base Oil Viscosity, 40°C | mm ² /s | 110 |
| | Thickener | | Lithium soap |
| | Density | g/cc | 0.86 |
| | NLGI | Class | 2 |
| ASTM D 217 | Worked Penetration | mm/10 | 265-295 |
| | Temperature Range | °C | -25 to +120 |
| ASTM D 566 | Drop Point | °C | +185 |
| DIN 51 807 | Water Resistance | | 0-90 |
| DIN 51 350 | Weld Scar under 800N load | mm | 0.8 |
| ASTM D 130 | Copper Strip Corrosion Test | | 1a |
| ASTM D 1264 | Water washout | % | <2.5 |

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

Manufactured by
ASV Multichemie Private Limited
W 46, TTC Industrial Area, MIDC Rabale,
Navi Mumbai 400 701 INDIA
Contact: +91 22 2764 2516
Email: info@asvmultichemie.com

Available Packaging

20 kg, 180 kg

Shelf Life

36 months from date of manufacture in sealed condition.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty. Product manufactured is for industrial use only.

WWW.ASVMULTICHEMIE.COM

ASV® MOLYSULF® PENETROIL® SHINY GALVA® VALV-KOTE® BRIGHT ZINK®
SPEZET® MOLYCHEM® TRIBOSULF® are Registered Trademarks of ASV MULTICHEMIE
PRIVATE LIMITED, INDIA.
ALL DATA OFFERED WITHOUT LIABILITY OR WARRANTY.