according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) M-55 DISPERSION

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.09.2015

 1.4
 08.10.2015
 1671515-00005
 Date of first issue: 19.03.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MOLYKOTE(R) M-55 DISPERSION

Product code : 0000000001206737, 00000000001206737

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Lubricants and lubricant additives

stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Dow Corning Europe S.A.

rue Jules Bordet - Parc Industriel - Zone C

B-7180 Seneffe

Telephone : English Tel: +49 611237507

Deutsch Tel: +49 611237500 Français Tel: +32 64511149 Italiano Tel: +32 64511170 Español Tel: +32 64511163

E-mail address of person responsible for the SDS

: sdseu@dowcorning.com

1.4 Emergency telephone number

Dow Corning (Barry U.K. 24h) Tél: +44 1446732350 Dow Corning (Wiesbaden 24h) Tél: +49 61122158 Dow Corning (Seneffe 24h) Tel: +32 64 888240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling:

EUH210 Safety data sheet available on request.

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Inorganic and organic compounds



MOLYKOTE(R) M-55 DISPERSION

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.09.2015

 1.4
 08.10.2015
 1671515-00005
 Date of first issue: 19.03.2015

dispersion

Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
Distillates (petroleum), solvent-	64742-65-0	Asp. Tox. 1; H304	>= 70 - < 90
dewaxed heavy paraffinic	265-169-7		
Distillates (petroleum), hy-	64742-54-7	Asp. Tox. 1; H304	>= 1 - < 10
drotreated heavy paraffinic	265-157-1		

SECTION 4: First aid measures

4.1 Description of first aid measures

Protection of first-aiders : No special precautions are necessary for first aid responders.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Exposure to combustion products may be a hazard to health.



MOLYKOTE(R) M-55 DISPERSION

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.09.2015

 1.4
 08.10.2015
 1671515-00005
 Date of first issue: 19.03.2015

Hazardous combustion prod-

ucts

: Carbon oxides Metal oxides Sulphur oxides

5.3 Advice for firefighters

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if nec-

essary. Use personal protective equipment.

Specific extinguishing meth-

ods

: Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Follow safe handling advice and personal protective equip-

ment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE



MOLYKOTE(R) M-55 DISPERSION

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.09.2015

 1.4
 08.10.2015
 1671515-00005
 Date of first issue: 19.03.2015

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety

practice

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep in properly labelled containers. Store in accordance with

the particular national regulations.

Advice on common storage : Do not store with the following product types:

Strong oxidizing agents

7.3 Specific end use(s)

Specific use(s) : These precautions are for room temperature handling. Use at

elevated temperature or aerosol/spray applications may re-

quire added precautions.

For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the

Dow Corning customer service group.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
Molybdenum sul-	1317-33-5	TWA	10 mg/m3	GB EH40
fide			(Molybdenum)	
		STEL	20 mg/m3	GB EH40
			(Molybdenum)	

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Distillates (petroleum), hy- drotreated heavy paraffinic	Oral	9.33 mg/kg

8.2 Exposure controls

Engineering measures

according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) M-55 DISPERSION

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.09.2015

 1.4
 08.10.2015
 1671515-00005
 Date of first issue: 19.03.2015

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:

Safety glasses

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Skin and body protection : Skin should be washed after contact.

Respiratory protection : Use respiratory protection unless adequate local exhaust ven-

tilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : black

Odour : slight

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

: > 35 °C

Flash point : 150 °C

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : 0.91

according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) M-55 DISPERSION

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.09.2015

 1.4
 08.10.2015
 1671515-00005
 Date of first issue: 19.03.2015

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : > 20.5 mm2/s

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Molecular weight : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of : Inhalation

exposure Sk

Skin contact Ingestion Eye contact

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) M-55 DISPERSION

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.09.2015

 1.4
 08.10.2015
 1671515-00005
 Date of first issue: 19.03.2015

Acute toxicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) M-55 DISPERSION

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.09.2015

 1.4
 08.10.2015
 1671515-00005
 Date of first issue: 19.03.2015

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

Remarks: Based on data from similar materials

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Test Type: Buehler Test Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Test Type: Buehler Test Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

Remarks: Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection Method: OECD Test Guideline 474

Result: negative

according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) M-55 DISPERSION

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.09.2015

 1.4
 08.10.2015
 1671515-00005
 Date of first issue: 19.03.2015

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Mouse

Application Route: Skin contact Exposure time: 78 weeks

Method: OECD Test Guideline 451

Result: negative

Carcinogenicity - Assess- : Classified based on DMSO extract content < 3% (Regulation

ment (EC) 1272/2008, Annex VI, Part 3, Note L)

Distillates (petroleum), hydrotreated heavy paraffinic:

Species: Mouse

Application Route: Skin contact Exposure time: 78 weeks

Method: OECD Test Guideline 451

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity - Assess- : Classified based on DMSO extract content < 3% (Regulation

ment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop- : Test Type: Embryo-foetal development



MOLYKOTE(R) M-55 DISPERSION

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.09.2015

 1.4
 08.10.2015
 1671515-00005
 Date of first issue: 19.03.2015

ment Species: Rat

Application Route: Skin contact Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

: Test Type: Embryo-foetal development

Species: Rat

Application Route: Skin contact Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit NOAEL: 1,000 mg/kg

Application Route: Skin contact Exposure time: 4 Weeks

Method: OECD Test Guideline 410

Remarks: Based on data from similar materials

Species: Rat

NOAEL: > 980 mg/m3

Application Route: inhalation (dust/mist/fume)

Exposure time: 4 Weeks

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species: Rabbit NOAEL: 1,000 mg/kg

Application Route: Skin contact Exposure time: 4 Weeks

Method: OECD Test Guideline 410

Remarks: Based on data from similar materials

Species: Rat

NOAEL: > 980 mg/m3

according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) M-55 DISPERSION

Version Revision Date: SDS Number: Date of last issue: 29.09.2015 08.10.2015 1671515-00005 Date of first issue: 19.03.2015 1.4

Application Route: inhalation (dust/mist/fume)

Exposure time: 4 Weeks

Aspiration toxicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Distillates (petroleum), hydrotreated heavy paraffinic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

: LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l Toxicity to fish

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to bacteria : NOEC: > 1.93 mg/l

> Exposure time: 10 min Method: DIN 38 412 Part 8

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

: NOEC: 10 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) M-55 DISPERSION

Version Revision Date: SDS Number: Date of last issue: 29.09.2015 08.10.2015 1671515-00005 Date of first issue: 19.03.2015 1.4

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

: EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 Toxicity to algae

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to bacteria : NOEC: > 1.93 mg/l

> Exposure time: 10 min Method: DIN 38 412 Part 8

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates (Chron-

NOEC: 10 mg/l Exposure time: 21 d

ic toxicity)

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Result: Not readily biodegradable. Biodegradability

Biodegradation: 2 - 8 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.

> Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods



MOLYKOTE(R) M-55 DISPERSION

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.09.2015

 1.4
 08.10.2015
 1671515-00005
 Date of first issue: 19.03.2015

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parlia-

ment and the Council concerning the export and import

of dangerous chemicals

: Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

: Not applicable

: Not applicable

Regulation (EC) No 850/2004 on persistent organic pol-

lutants

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

DOW CORNING

MOLYKOTE(R) M-55 DISPERSION

Version Revision Date: SDS Number: Date of last issue: 29.09.2015
1.4 08.10.2015 Date of first issue: 19.03.2015

The components of this product are reported in the following inventories:

KECI : All ingredients listed, exempt or notified.

TCSI : All ingredients listed or exempt.

REACH : All ingredients (pre-)registered or exempt.

AICS : All ingredients listed or exempt.

IECSC : All ingredients listed or exempt.

PICCS : All ingredients listed or exempt.

DSL : All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the Ca-

nadian Domestic Substances List (DSL).

NZIoC : All ingredients listed or exempt.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of H-Statements

H304 : May be fatal if swallowed and enters airways.

Full text of other abbreviations

Asp. Tox. : Aspiration hazard

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan): ErCx -Concentration associated with x% growth rate response: GHS - Globally Harmonized System: GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No

DOW CORNING

MOLYKOTE(R) M-55 DISPERSION

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.09.2015

 1.4
 08.10.2015
 1671515-00005
 Date of first issue: 19.03.2015

Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data

Sheet

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN