

Liquid spray grease

Description

MOLYSLIP LQG is a multi-purpose lubricant consisting of a colloidal suspension of molybdenum disulphide in a semi-fluid grease. The aerosol spray application and ability to penetrate ensures effective lubrication is delivered into even the most inaccessible areas. LQG combines the advantages of solid grease with those of a lubricating oil – the sub-micron particle size molybdenum disulphide reduces friction and wear and the effective corrosion inhibitors protect components from harsh environments.

MOLYSLIP LQG is suitable for use in a wide range of applications including bearings, slides, pins, bushes and other mechanisms requiring long term effective lubrication.

Features and benefits

- Convenient aerosol application
- Excellent penetration properties
- Good load carrying and anti-wear
- Effective protection against corrosion
- 360° spray can

Instructions for use

Shake can before use. Apply from a suitable distance. Do not spray near naked flames or incandescent material.

Packaging

400 ml aerosol

Technical data

LQG

The logo for MOLYSLIP, featuring the brand name in a bold, italicized, sans-serif font with a registered trademark symbol, set against a red rectangular background.

Technical data (typical values)

Property	Test method	Result
Appearance	-	Semi-fluid grey/black grease
Lubricating solids	-	MoS ₂
Operating temperature range	-	-35°C to +90°C

Storage

Store MOLYSLIP LQG out of direct sunlight. Storage temperature should be controlled to between 5°C and 35°C.

The product information in this publication is based on knowledge and experience at the time of printing. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.
Issue date 06-17