




OKS 2511 - Product Information

Fields of Application:

Repair of galvanising interrupted or damaged during welding, drilling or cutting (hot galvanising, electrogalvanising or flame-spray galvanising). Priming of ferrous metals before further painting (zinc dust priming) in place of galvanising which cannot be carried out. For example, in vehicle and ship repairs, in steel building construction, civil engineering and bridge building, in tank and overhead line construction, on grids, fence and traffic signal posts, exhaust systems, drain gutters etc.

OKS 2511 Zinc Coating, Spray



Advantages and Benefits:

Highly effective due to active, cathodic corrosion protection. Excellently suited for initial layer build-up of long-term coating systems. Broad range of uses in temporary and permanent corrosion protection for all thermally loaded parts, which are also exposed to special corrosion susceptibilities. Economical due to low consumption and self-cleaning spray valve (no overhead "spraying clear" necessary, and therefore no solvent and propellant gas losses). Supplements galvanising and forms a micro-rough adhesive surface for subsequent painting. Also suitable for spot welding.

Application:

For best results clean the surfaces, first mechanically and then with OKS 2610/OKS 2611 Universal Cleaner. The surfaces have to be metallic blank and dry. Shake well before use. Spray a thin layer evenly from 20-30 cm distance onto the prepared surface (cross-wise or circularly). Avoid local excess. Drying and curing conditions acc. to the following technical data. For thicker layers repeat the procedure. It is not possible to prime on OKS 2511. Do not use below +10°C and humidity > 80%. For additional questions please contact our Technical Department.

Additional Information:

Packaging (Article number):
- 500 ml Spray (02511005)

Version:
E-02.1/07

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark



OKS 2511 Zinc Coating, Spray

Technical Data

	Norm	Conditions	Unit	Value
Solid Lubricants				
Type				Zinc, 98,5% pure
Entire share	DIN 51 814	cured	Mass-%	ca. 38
Binder				
Type				synthetic resin mixture
Solvent				
Type				Solventmixture
Film Layer				
Optimal layer thickness	DIN 50 981/50 984	DIN 50 982-2	µm	60 - 80
Application temperature			°C	Room temperature
Drying time		at 20°C	min	appr. 15
Curing time		at 20 °C	h	10 - 12
Varnishing time		at 20 °C	h	appr. 12
Surface coverage			m ² /tin	appr. 3
Application Data				
Density	DIN EN ISO 3838	+20°C	g/ml	1,1
Colour				zinc grey
Application Temperatures				
Upper application temperature			°C	400
Corrosion Protection Tests				
Salt spray test	DIN 50 021	> 70 µm	h	700

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. © = Registered Trademark