

Soudal 110 LQ Contact Adhesive

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Soudal 110 LQ Contact Adhesive
 Registration number REACH : Not applicable (mixture)
 Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses
 Adhesive

1.2.2 Uses advised against
 No uses advised against known

Manufacturer of the product

SODAL N.V.
 Everdongenlaan 18-20
 B-2300 Turnhout
 ☎ +32 14 42 42 31
 ☐ +32 14 42 65 14
 msds@soudal.com

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):
 +32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Flam. Liq.	category 2	H225: Highly flammable liquid and vapour.
Repr.	category 2	H361d: Suspected of damaging the unborn child.
Asp. Tox.	category 1	H304: May be fatal if swallowed and enters airways.
STOT RE	category 2	H373: May cause damage to organs through prolonged or repeated exposure if inhaled.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
Skin Irrit.	category 2	H315: Causes skin irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Chronic	category 2	H411: Toxic to aquatic life with long lasting effects.

2.2. Label elements



Contains: toluene; naphtha (petroleum), hydrotreated light.

Signal word Danger

H-statements

H225 Highly flammable liquid and vapour.
 H361d Suspected of damaging the unborn child.

Soudal 110 LQ Contact Adhesive

H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
P-statements	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves, protective clothing and eye protection/face protection.
P271	Use only outdoors or in a well-ventilated area.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulation.

2.3. Other hazards

- May build up electrostatic charges: risk of ignition
- Gas/vapour spreads at floor level: ignition hazard

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
acetone 01-2119471330-49	67-64-1 200-662-2	1%<C<15%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Constituent
toluene 01-2119471310-51	108-88-3 203-625-9	1%<C<40%	Flam. Liq. 2; H225 Repr. 2; H361d Asp. Tox. 1; H304 STOT RE 2; H373 Skin Irrit. 2; H315 STOT SE 3; H336	(1)(2)(10)	Constituent
naphtha (petroleum), hydrotreated light 01-2119475133-43	64742-49-0 265-151-9	1%<C<40%	Flam. Liq. 2; H225 Repr. 2; H361d Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(10)	Constituent

- (1) For H-statements in full: see heading 16
 (2) Substance with a Community workplace exposure limit
 (10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Wash immediately with lots of water. Soap may be used. Take victim to a doctor if irritation persists.

After eye contact:

Rinse immediately with plenty of water. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Do not induce vomiting. Consult a doctor/medical service if you feel unwell.

Publication date: 2016-05-30

Soudal 110 LQ Contact Adhesive

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

Narcosis. EXPOSURE TO HIGH CONCENTRATIONS: Irritation of the respiratory tract. Headache. Vomiting. Nausea.

After skin contact:

Tingling/irritation of the skin. ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Cracking of the skin.

After eye contact:

Irritation of the eye tissue. Lacrimation. Redness of the eye tissue.

After ingestion:

Risk of aspiration pneumonia. Symptoms similar to those listed under inhalation.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Water spray. Alcohol-resistant foam. BC powder. Carbon dioxide.

5.1.2 Unsuitable extinguishing media:

No unsuitable extinguishing media known. Solid water jet ineffective as extinguishing medium.

5.2. Special hazards arising from the substance or mixture

On burning: release of harmful gases/vapours e.g.: carbon monoxide - carbon dioxide.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective goggles. Head/neck protection. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Protective goggles. Head/neck protection. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Contain released product. Dam up the liquid spill. Try to reduce evaporation. Prevent soil and water pollution. Prevent spreading in sewers. Use appropriate containment to avoid environmental contamination.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material sand/earth. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Keep away from naked flames/heat. Insufficient ventilation: keep naked flames/sparks away. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: take precautions against electrostatic charges. Gas/vapour heavier than air at 20°C. Observe strict hygiene. Keep container tightly closed. Remove contaminated clothing immediately. Do not discharge the waste into the drain.

Publication date: 2016-05-30

Soudal 110 LQ Contact Adhesive

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: 5 - 25 °C. Store in a cool area. Keep out of direct sunlight. Ventilation at floor level. Fireproof storeroom. Keep locked up. Unauthorized persons are not admitted. Meet the legal requirements. Keep out of direct sunlight. Max. storage time: 1 year(s).

7.2.2 Keep away from:

Heat sources, ignition sources, oxidizing agents.

7.2.3 Suitable packaging material:

Metal.

7.2.4 Non suitable packaging material:

Synthetic material.

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

Acetone	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	500 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1210 mg/m ³
Toluene	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	50 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	192 mg/m ³
	Short time value (Indicative occupational exposure limit value)	100 ppm
	Short time value (Indicative occupational exposure limit value)	384 mg/m ³

Belgium

Acétone	Time-weighted average exposure limit 8 h	500 ppm
	Time-weighted average exposure limit 8 h	1210 mg/m ³
	Short time value	1000 ppm
	Short time value	2420 mg/m ³
Toluène	Time-weighted average exposure limit 8 h	20 ppm
	Time-weighted average exposure limit 8 h	77 mg/m ³
	Short time value	100 ppm
	Short time value	384 mg/m ³

The Netherlands

Aceton	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	501 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	1210 mg/m ³
	Short time value (Public occupational exposure limit value)	1002 ppm
	Short time value (Public occupational exposure limit value)	2420 mg/m ³
Tolueen	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	39 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	150 mg/m ³
	Short time value (Public occupational exposure limit value)	100 ppm
	Short time value (Public occupational exposure limit value)	384 mg/m ³

France

Acétone	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	500 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	1210 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	1000 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	2420 mg/m ³

Publication date: 2016-05-30

Soudal 110 LQ Contact Adhesive

Toluène	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	20 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	76.8 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	100 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	384 mg/m ³

Germany

Aceton	Time-weighted average exposure limit 8 h (TRGS 900)	500 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1200 mg/m ³
Toluol	Time-weighted average exposure limit 8 h (TRGS 900)	50 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	190 mg/m ³

UK

Acetone	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	500 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1210 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	1500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	3620 mg/m ³
Toluene	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	50 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	191 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	100 ppm
	Short time value (Workplace exposure limit (EH40/2005))	384 mg/m ³

USA (TLV-ACGIH)

Acetone	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	250 ppm
	Short time value (TLV - Adopted Value)	500 ppm
Toluene	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	20 ppm

b) National biological limit values

If limit values are applicable and available these will be listed below.

Germany

Aceton (Aceton)	Urin: expositionsende, bzw. schichtende	80 mg/l	11/2012 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG
Toluol (o-Kresol (nach Hydrolyse))	Urin: bei langzeitexposition: nach mehreren vorangegangenen schichten expositionsende, bzw. schichtende	1,5 mg/l	11/2012 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG
Toluol (Toluol)	Vollblut: expositionsende, bzw. schichtende	600 µg/l	11/2012 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG

USA (BEI-ACGIH)

Acetone (Acetone)	Urine: end of shift	20 mg/L	Nonspecific - Intended changes
Acetone (Acetone)	Urine: end of shift	25 mg/L	
Toluene (o-Cresol)	Urine: end of shift	0,3 mg/g creatinine	
Toluene (Toluene)	Blood: prior to last shift of workweek	0,02 mg/L	
Toluene (Toluene)	urine: end of shift	0,03 mg/L	

8.1.2 Sampling methods

If applicable and available it will be listed below.

Acetone (ketones 1)	NIOSH	1300
Acetone (ketones I)	NIOSH	2555
Acetone (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
Acetone (Volatile Organic compounds)	NIOSH	2549
ACETONE and METHYL ETHYL KETONE in urine	NIOSH	8319
Acetone	OSHA	69
Toluene (Hydrocarbons, aromatic)	NIOSH	1501
Toluene (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
Toluene (Volatile Organic compounds)	NIOSH	2549
Toluene in blood	NIOSH	8007
Toluene	NIOSH	4000
Toluene	NIOSH	8002

Publication date: 2016-05-30

Soudal 110 LQ Contact Adhesive

Toluene	NIOSH	95-117
Toluene	OSHA	111

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 DNEL/PNEC values

DNEL/DMEL - Workers

acetone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Acute local effects inhalation	2420 mg/m ³	
	Long-term systemic effects dermal	186 mg/kg bw/day	
	Long-term systemic effects inhalation	1210 mg/m ³	

toluene

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	192 mg/m ³	
	Acute systemic effects inhalation	384 mg/m ³	
	Long-term local effects inhalation	192 mg/m ³	
	Acute local effects inhalation	384 mg/m ³	
	Long-term systemic effects dermal	384 mg/kg bw/day	

DNEL/DMEL - General population

acetone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects dermal	62 mg/kg bw/day	
	Long-term systemic effects inhalation	200 mg/m ³	
	Long-term systemic effects oral	62 mg/kg bw/day	

toluene

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	56.5 mg/m ³	
	Acute systemic effects inhalation	226 mg/m ³	
	Long-term local effects inhalation	56.5 mg/m ³	
	Acute local effects inhalation	226 mg/m ³	
	Long-term systemic effects dermal	226 mg/kg bw/day	
	Long-term systemic effects oral	8.13 mg/kg bw/day	

PNEC

acetone

Compartments	Value	Remark
Fresh water	10.6 mg/l	
Marine water	1.06 mg/l	
Aqua (intermittent releases)	21 mg/l	
Fresh water sediment	30.4 mg/kg sediment dw	
Marine water sediment	3.04 mg/kg sediment dw	
Soil	33.3 mg/kg soil dw	
STP	100 mg/l	

toluene

Compartments	Value	Remark
Fresh water	0.68 mg/l	
Marine water	0.68 mg/l	
Aqua (intermittent releases)	0.68 mg/l	
STP	13.61 mg/l	
Fresh water sediment	16.39 mg/kg sediment dw	
Marine water sediment	16.39 mg/kg sediment dw	
Soil	2.89 mg/kg soil dw	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Insufficient ventilation: keep naked flames/sparks away. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: take precautions against electrostatic charges. Measure the concentration in the air regularly. Work under local exhaust/ventilation.

8.2.2 Individual protection measures, such as personal protective equipment

Publication date: 2016-05-30

Soudal 110 LQ Contact Adhesive

Observe strict hygiene. Keep container tightly closed. Do not eat, drink or smoke during work.

a) Respiratory protection:

Wear gas mask with filter type A if conc. in air > exposure limit.

b) Hand protection:

Gloves.

- materials (good resistance)

Neoprene.

c) Eye protection:

Protective goggles.

d) Skin protection:

Head/neck protection. Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Liquid
Odour	Characteristic odour
Odour threshold	No data available
Colour	Dark amber
Particle size	Not applicable (liquid)
Explosion limits	No data available
Flammability	Highly flammable liquid and vapour.
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	No data available
Boiling point	No data available
Flash point	< -23 °C
Evaporation rate	No data available
Relative vapour density	> 1
Vapour pressure	No data available
Solubility	water ; insoluble
Relative density	0.85 ; 20 °C
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
pH	No data available

9.2. Other information

Surface tension	27.5 mN/m ; 20 °C
Absolute density	850 kg/m ³ ; 20 °C

SECTION 10: Stability and reactivity

10.1. Reactivity

May build up electrostatic charges: risk of ignition. May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. No data available.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Keep away from naked flames/heat. Insufficient ventilation: keep naked flames/sparks away. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: take precautions against electrostatic charges.

10.5. Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

On burning: release of harmful gases/vapours e.g.: carbon monoxide - carbon dioxide.

Publication date: 2016-05-30

Soudal 110 LQ Contact Adhesive

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

Soudal 110 LQ Contact Adhesive

No (test) data on the mixture available

acetone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	5800 mg/kg		Rat (female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	20000 mg/kg		Rabbit (male)	Experimental value	
Dermal	LD50		> 7426 mg/kg bw		Rabbit (female)	Weight of evidence	
Inhalation (vapours)	LC50	Other	76 mg/l	4 h	Rat (female)	Experimental value	
Inhalation (vapours)	LCL0	Other	16000 ppm	4 h	Rat	Experimental value	

toluene

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral (one dose)	LD50	Equivalent to EU Method B.1	5580 mg/kg bw		Rat (male)	Experimental value	
Dermal	LD50	Other	> 5000 mg/kg bw	24 h	Rabbit (male)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	25.7 mg/l air	4 h	Rat (male)	Experimental value	

naphtha (petroleum), hydrotreated light

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg bw		Rat (male/female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 2000 mg/kg bw	24 h	Rabbit (male/female)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 5740 mg/m ³	4 h	Rat (male/female)	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Not classified for acute toxicity

Corrosion/irritation

Soudal 110 LQ Contact Adhesive

No (test) data on the mixture available

acetone

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	OECD 405		24; 48; 72 hours	Rabbit	Weight of evidence	
Skin	Not irritating	Other	3 day(s)	24; 48; 72 hours	Guinea pig	Weight of evidence	
Inhalation	Slightly irritating	Human observation study	20 minutes		Human	Literature	

toluene

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405	7 day(s)	24; 48; 72 hours	Rabbit	Experimental value	Single treatment
Skin	Irritating	EU Method B.4	4 h	24; 48; 72 hours	Rabbit	Experimental value	

naphtha (petroleum), hydrotreated light

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		1; 24; 48; 72 hours	Rabbit	Experimental value	Single treatment
Skin	Irritating	Equivalent to OECD 404	24 h	24; 72 hours	Rabbit	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Publication date: 2016-05-30

Soudal 110 LQ Contact Adhesive

Causes skin irritation.
Causes serious eye irritation.
Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

Soudal 110 LQ Contact Adhesive

No (test)data on the mixture available

acetone

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Guinea pig maximisation test		48 hours	Hamster (female)	Experimental value	
Skin	Not sensitizing	Human observation			Human	Literature	

toluene

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406	72 h	24; 48 hours	Guinea pig (female)	Experimental value	

naphtha (petroleum), hydrotreated light

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406		24; 48 hours	Guinea pig (male)	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Not classified as sensitizing for inhalation
Not classified as sensitizing for skin

Specific target organ toxicity

Soudal 110 LQ Contact Adhesive

No (test)data on the mixture available

acetone

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral	NOAEL	Equivalent to OECD 408	20 mg/l		No effect	13 week(s)	Mouse (male/female)	Experimental value
Dermal								Not relevant, expert judgement
Inhalation (vapours)	NOAEC	Other	19000 ppm		No effect	8 week(s)	Rat (male)	Literature
Inhalation (vapours)		Human observation study	361 ppm	Central nervous system	neurotoxic effects	2 day(s)	Human	Inconclusive, insufficient data

toluene

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral	NOAEL	Equivalent to OECD 408	625 mg/kg bw/day		No effect	13 weeks (daily, 5 days/week)	Mouse (male/female)	Experimental value
Dermal								Data waiving
Inhalation (vapours)	LOAEC	Equivalent to OECD 453	600 ppm	Respiratory tract	Erosion/degeneration nasal epithelia	103 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value
Inhalation	NOAEC	Human observation	50 ppm	Central nervous system	No effect	4.5 h	Human (male)	Experimental value

naphtha (petroleum), hydrotreated light

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOEL		< 500 mg/kg bw/day		No effect	4 weeks (5 days/week)	Rat (male)	
Dermal	NOAEL	Equivalent to OECD 411	< 37.5 ml			13 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value
Inhalation (vapours)	NOAEL	OECD 413	47280 mg/m ³	Respiratory tract	No effect	13 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value

Judgement is based on the relevant ingredients

Publication date: 2016-05-30

Soudal 110 LQ Contact Adhesive

Conclusion

May cause damage to organs through prolonged or repeated exposure if inhaled.
May cause drowsiness or dizziness.

Mutagenicity (in vitro)

Soudal 110 LQ Contact Adhesive

No (test)data on the mixture available

acetone

Result	Method	Test substrate	Effect	Value determination
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value
Negative	Equivalent to OECD 473	Chinese hamster ovary (CHO)	No effect	Experimental value

toluene

Result	Method	Test substrate	Effect	Value determination
Negative	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value

naphtha (petroleum), hydrotreated light

Result	Method	Test substrate	Effect	Value determination
Negative	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value

Mutagenicity (in vivo)

Soudal 110 LQ Contact Adhesive

No (test)data on the mixture available

acetone

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative		13 week(s)	Mouse (male/female)		Literature

toluene

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Other		Rat		Experimental value
Negative	Equivalent to OECD 478	8 weeks (6h/day, 5 days/week)	Mouse (male)		Experimental value

Judgement is based on the relevant ingredients

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

Soudal 110 LQ Contact Adhesive

No (test)data on the mixture available

acetone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Dermal	NOEL	Other	79 mg	51 week(s)	Mouse (female)	No effect		Literature

toluene

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOAEC	Equivalent to OECD 453	1200 ppm	103 weeks (6h/day, 5 days/week)	Rat (male/female)	No effect		Experimental value
Dermal	NOAEL	Carcinogenic toxicity study	0.05 ml (twice a week)		Mouse (male)	No effect		Experimental value

naphtha (petroleum), hydrotreated light

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Dermal	NOAEL	Equivalent to OECD 451	0.05 ml	102 weeks (3 times/week)	Mouse (male)	No carcinogenic effect		Experimental value

Judgement is based on the relevant ingredients

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

Soudal 110 LQ Contact Adhesive

No (test)data on the mixture available

Publication date: 2016-05-30

Soudal 110 LQ Contact Adhesive

acetone

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEC	Equivalent to OECD 414	11000 ppm	6 days (gestation, daily) - 19 days (gestation, daily)	Rat (male/female)			Experimental value
Effects on fertility	NOAEL	Other	900 mg/kg bw/day	13 week(s)	Rat (male)	No effect		Literature

toluene

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEC	EPA OTS 798.4350	750 ppm	20 days (6h/day)	Rat (female)	No effect		Experimental value
Maternal toxicity	NOAEC	EPA OTS 798.4350	750 ppm	20 days (6h/day)	Rat (female)	Maternal toxicity		Experimental value
Effects on fertility	NOAEC (P)	OECD 416	2000 ppm	11 weeks (6h/day, 7 days/week)	Rat (male/female)	No effect		Experimental value
	NOAEC (F1)	OECD 416	500 ppm	11 weeks (6h/day, 7 days/week)	Rat (male/female)	No effect		Experimental value
	NOAEC (F2)	OECD 416	500 ppm	11 weeks (6h/day, 7 days/week)	Rat (male/female)	No effect		Experimental value

naphtha (petroleum), hydrotreated light

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOEL	Equivalent to OECD 414	< 100 mg/kg	25 days (1x/day)	Rat	No effect	Skin	Experimental value

Classification is based on the relevant ingredients

Conclusion

Suspected of damaging the unborn child.

Aspiration hazard

Classification is based on the relevant ingredients

May be fatal if swallowed and enters airways.

Toxicity other effects

Soudal 110 LQ Contact Adhesive

No (test) data on the mixture available

acetone

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
			Skin	Skin dryness or cracking			Literature study

Chronic effects from short and long-term exposure

Soudal 110 LQ Contact Adhesive

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Impairment of the nervous system.

SECTION 12: Ecological information

12.1. Toxicity

Soudal 110 LQ Contact Adhesive

No (test) data on the mixture available

Publication date: 2016-05-30

Soudal 110 LQ Contact Adhesive

acetone

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	EU Method C.1	5540 mg/l	96 h	Salmo gairdneri	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity invertebrates	LC50	Other	12600 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	EC50		> 7000 mg/l	96 h	Selenastrum capricornutum	Static system	Fresh water	Experimental value; Nominal concentration

toluene

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		5.5 mg/l	96 h	Oncorhynchus kisutch	Flow-through system	Fresh water	Experimental value
Acute toxicity invertebrates	LC50	US EPA	3.78 mg/l	48 h	Ceriodaphnia dubia		Fresh water	Experimental value
Toxicity algae and other aquatic plants	EC50		12.5 mg/l	72 h	Selenastrum capricornutum			Literature study
Long-term toxicity fish	NOEC		1.39 mg/l	40 day(s)	Oncorhynchus kisutch	Flow-through system	Fresh water	Experimental value; Growth rate
Long-term toxicity aquatic invertebrates	NOEC	US EPA	0.74 mg/l	7 day(s)	Ceriodaphnia dubia		Fresh water	Experimental value; Reproduction
Toxicity aquatic micro-organisms	EC50		84 mg/l	24 h	Nitrosomonas	Static system	Fresh water	Experimental value

naphtha (petroleum), hydrotreated light

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	10 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity invertebrates	EL50	OECD 202	4.5 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EL50	OECD 201	3.1 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOELR	OECD 204	2.6 mg/l	14 day(s)	Pimephales promelas	Semi-static system	Fresh water	Experimental value; GLP
Long-term toxicity aquatic invertebrates	NOELR	OECD 211	2.6 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; GLP
Toxicity aquatic micro-organisms	EC50		15.41 mg/l	40 h	Tetrahymena pyriformis		Fresh water	QSAR

Classification is based on the relevant ingredients

Conclusion

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

acetone

Biodegradation water

Method	Value	Duration	Value determination
OECD 301B: CO2 Evolution Test	90.9 %	28 day(s)	Experimental value

toluene

Biodegradation water

Method	Value	Duration	Value determination
OECD 301C: Modified MITI Test (I)	100 %	14 day(s)	Experimental value

Half-life soil (t1/2 soil)

Method	Value	Primary degradation/mineralisation	Value determination
	2.6 day(s)		Literature study

Publication date: 2016-05-30

Soudal 110 LQ Contact Adhesive

naphtha (petroleum), hydrotreated light

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F: Manometric Respirometry Test	77.05 %; GLP	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
			Data waiving

Phototransformation water (DT50 water)

Method	Value	Conc. OH-radicals	Value determination
			Data waiving

Biodegradation soil

Method	Value	Duration	Value determination
			Data waiving

Conclusion

Contains readily biodegradable component(s)

12.3. Bioaccumulative potential

Soudal 110 LQ Contact Adhesive

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

acetone

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		0.69		Pisces	

BCF other aquatic organisms

Parameter	Method	Value	Duration	Species	Value determination
BCF	BCFWIN	3			Calculated value

Log Kow

Method	Remark	Value	Temperature	Value determination
		-0.24		Test data

toluene

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		90	72 h	Leuciscus idus	Experimental value

Log Kow

Method	Remark	Value	Temperature	Value determination
Other		2.73	20 °C	Experimental value

naphtha (petroleum), hydrotreated light

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
					Data waiving

BCF other aquatic organisms

Parameter	Method	Value	Duration	Species	Value determination
					Data waiving

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

Conclusion

No straightforward conclusion can be drawn based upon the available numerical values

12.4. Mobility in soil

naphtha (petroleum), hydrotreated light

(log) Koc

Parameter	Method	Value	Value determination
log Koc	PCKOCWIN v1.66	1.783 - 2.36	Calculated value

Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	93.02 %		0.81 %	0.34 %	5.83 %	Calculated value

Publication date: 2016-05-30

Soudal 110 LQ Contact Adhesive

Conclusion

Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Other adverse effects

Soudal 110 LQ Contact Adhesive

Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

Ground water

Ground water pollutant

toluene

Ground water

Ground water pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 04 09* (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants containing organic solvents or other hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Incinerate under surveillance with energy recovery. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Should not be landfilled with household waste. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1. UN number

UN number	1133
-----------	------

14.2. UN proper shipping name

Proper shipping name	Adhesives
----------------------	-----------

14.3. Transport hazard class(es)

Hazard identification number	33
------------------------------	----

Class	3
-------	---

Classification code	F1
---------------------	----

14.4. Packing group

Packing group	II
---------------	----

Labels	3
--------	---

14.5. Environmental hazards

Environmentally hazardous substance mark	yes
--	-----

14.6. Special precautions for user

Special provisions	640D
--------------------	------

Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
--------------------	---

Rail (RID)

14.1. UN number

UN number	1133
-----------	------

14.2. UN proper shipping name

Proper shipping name	Adhesives
----------------------	-----------

Publication date: 2016-05-30

Soudal 110 LQ Contact Adhesive

14.3. Transport hazard class(es)

Hazard identification number	33
Class	3
Classification code	F1

14.4. Packing group

Packing group	II
Labels	3

14.5. Environmental hazards

Environmentally hazardous substance mark	yes
--	-----

14.6. Special precautions for user

Special provisions	640D
Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Inland waterways (ADN)

14.1. UN number

UN number	1133
-----------	------

14.2. UN proper shipping name

Proper shipping name	Adhesives
----------------------	-----------

14.3. Transport hazard class(es)

Class	3
Classification code	F1

14.4. Packing group

Packing group	II
Labels	3

14.5. Environmental hazards

Environmentally hazardous substance mark	yes
--	-----

14.6. Special precautions for user

Special provisions	640D
Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Sea (IMDG/IMSBC)

14.1. UN number

UN number	1133
-----------	------

14.2. UN proper shipping name

Proper shipping name	Adhesives
----------------------	-----------

14.3. Transport hazard class(es)

Class	3
-------	---

14.4. Packing group

Packing group	II
Labels	3

14.5. Environmental hazards

Marine pollutant	P
Environmentally hazardous substance mark	yes

14.6. Special precautions for user

Special provisions	
Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Annex II of MARPOL 73/78	Not applicable, based on available data
--------------------------	---

Air (ICAO-TI/IATA-DGR)

14.1. UN number

UN number	1133
-----------	------

14.2. UN proper shipping name

Proper shipping name	Adhesives
----------------------	-----------

14.3. Transport hazard class(es)

Class	3
-------	---

14.4. Packing group

Packing group	II
Labels	3

14.5. Environmental hazards

Publication date: 2016-05-30

Soudal 110 LQ Contact Adhesive

Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	A3
Passenger and cargo transport: limited quantities: maximum net quantity per packaging	1 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
25 % - 80 %	
212.5 g/l - 680 g/l	

Indicative occupational exposure limit values (Directive 98/24/EC, 2000/39/EC and 2009/161/EU)

Product name	Skin resorption
Toluene	Skin

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
acetone toluene naphtha (petroleum), hydrotreated light	Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects. 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with R65 or H304. 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010. 6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public. 7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'
acetone toluene naphtha (petroleum), hydrotreated light	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopee" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: "For professional users only". 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC. 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
toluene	Toluene	Shall not be placed on the market, or used, as a substance or in mixtures in a concentration

Publication date: 2016-05-30

Soudal 110 LQ Contact Adhesive

equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

National legislation Belgium

Soudal 110 LQ Contact Adhesive

No data available

toluene

Résorption peau	Toluène; D: La mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air.
-----------------	--

National legislation The Netherlands

Soudal 110 LQ Contact Adhesive

Waste identification (the Netherlands)	LWCA (the Netherlands): KGA category 03
--	---

Waterbezikbaarheid	1 Z (2)
--------------------	------------

toluene

SZW - List of reprotoxic substances (development)	Suspected of damaging the unborn child.
---	---

National legislation France

Soudal 110 LQ Contact Adhesive

No data available

toluene

VME - Risque de pénétration percutanée	Toluène; PP
--	-------------

National legislation Germany

Soudal 110 LQ Contact Adhesive

WGK	3; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4)
-----	---

acetone

TA-Luft	5.2.5
---------	-------

TRGS900 - Risiko der Fruchtschädigung	Aceton; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
---------------------------------------	---

toluene

TA-Luft	5.2.5; I
---------	----------

TRGS900 - Risiko der Fruchtschädigung	Toluol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
---------------------------------------	---

Hautresorptive Stoffe	Toluol; H; Hautresorptiv
-----------------------	--------------------------

naphtha (petroleum), hydrotreated light

TA-Luft	5.2.5; I
---------	----------

National legislation United Kingdom

Soudal 110 LQ Contact Adhesive

No data available

toluene

Skin absorption	Toluene; Sk
-----------------	-------------

Other relevant data

Soudal 110 LQ Contact Adhesive

No data available

acetone

TLV - Carcinogen	Acetone; A4
------------------	-------------

toluene

TLV - Carcinogen	Toluene; A4
------------------	-------------

IARC - classification	3; Toluene
-----------------------	------------

15.2. Chemical safety assessment

No chemical safety assessment is required.

SECTION 16: Other information

Full text of any H-statements referred to under headings 2 and 3:

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

Publication date: 2016-05-30

Soudal 110 LQ Contact Adhesive

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs (central nervous system) through prolonged or repeated exposure if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

H411 Toxic to aquatic life with long lasting effects.

(*) = INTERNAL CLASSIFICATION BY BIG

PBT-substances = persistent, bioaccumulative and toxic substances

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Publication date: 2016-05-30